

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A scanning microscope comprising:

a laser ~~[[,]]~~ configured to generate light having a wavelength range;

an optical means for imaging light generated by the laser onto a specimen;
and

an optical component positioned between the laser and the optical means,

wherein the light generated by the laser passes through the optical
component ~~whereby~~ , and

wherein the optical component spectrally spreads the light passing through is
configured to increase said wavelength range of said light to a substantial portion of
the entire visible wavelength range.
2. (Original) The scanning microscope as defined in Claim 1, wherein
the optical component is photonic band-gap material.
3. (Original) The scanning microscope as defined in Claim 2, wherein
the photonic band-gap material is configured as a light-guiding fiber.
4. (Original) The scanning microscope as defined in Claim 1, wherein
the optical component is configured as a tapered light-guiding fiber.
5. (Original) The scanning microscope as defined in Claim 1, wherein
the laser is a pulsed laser.
6. (Original) The scanning microscope as defined in Claim 1, wherein
means for attenuating at least a portion of at least one wavelength of the light
emerging from the optical component is arranged after the optical component.

7. (Previously Presented) The scanning microscope as defined in Claim 6, wherein the means for attenuating comprises at least one of a spectrally selective filter, a dichroic filter, an acoustooptical tunable filter (AOTF), acoustooptical deflector (AOD), and an LCD attenuator.

8. (Original) The scanning microscope as defined in Claim 1, further comprising:

means for light output stabilization configured as a control loop.

9. (Currently Amended) A confocal scanning microscope comprising:

a laser ~~[[,]]~~ configured to generate light having a wavelength range;

an optical means for imaging light generated by the laser onto a specimen ~~[[,]]~~

;

~~a detector for receiving light coming~~ configured to receive light from the specimen ~~[[,]]~~ ; and

an optical component positioned between the laser and the optical means,

wherein the light generated by the laser passes through the optical component, ~~whereby~~

wherein the optical component spectrally spreads the light passing through is configured to increase said wavelength range of said light to a substantial portion of the entire visible wavelength range, and

wherein the optical component comprises an illumination pinhole through which the specimen is illuminated by the light emerging from the optical component.

10. (Original) The confocal scanning microscope as defined in Claim 9, wherein the optical component is photonic band-gap material.

11. (Original) The scanning microscope as defined in Claim 10, wherein the photonic band-gap material is configured as a light-guiding fiber.

12. (Withdrawn) The confocal scanning microscope as defined in Claim 11, wherein the light-guiding fiber defines an exit end which serves as the illumination pinhole.

13. (Original) The confocal scanning microscope as defined in Claim 9, wherein the optical component is configured as a tapered light-guiding fiber.

14. (Withdrawn) The confocal scanning microscope as defined in Claim 13, wherein the tapered light-guiding fiber defines an exit end which serves as the illumination pinhole.

15. (Original) The confocal scanning microscope as defined in Claim 9, wherein the laser is a pulsed laser.

16. (Original) The confocal scanning microscope as defined in Claim 9, wherein means for attenuating at least a portion of at least one wavelength of the light emerging from the optical component is arranged after the optical component.

17. (Previously Presented) The confocal scanning microscope as defined in Claim 16, wherein the means for attenuating comprises at least one of a spectrally selective filter, a dichroic filter, an acoustooptical tunable filter (AOTF), acoustooptical deflector (AOD), and an LCD attenuator.

18. (Original) The confocal scanning microscope as defined in Claim 9, further comprising: means for light output stabilization configured as a control loop.

19. – 27. (Canceled)

28. (Currently Amended) A scanning microscope comprising:

a pulsed laser configured to generate light having a wavelength range;

an optical means for imaging light generated by the pulsed laser onto a specimen; and

a light-guiding fiber, made of photonic band-gap material, positioned between the pulsed laser and the optical means,

wherein the light generated by the pulsed laser passes through the light-guiding fiber, and

~~whereby wherein~~ the light-guiding fiber ~~spectrally spreads the light passing through~~ is configured to increase said wavelength range of said light to a substantial portion of the entire visible wavelength range.

29. (Original) The scanning microscope as defined in Claim 28, wherein the scanning microscope is a confocal scanning microscope.

30. (Currently Amended) A scanning microscope comprising:
a pulsed laser ~~[[,]]~~ configured to generate light having a wavelength range;

an optical means for imaging light generated by the pulsed laser onto a specimen ~~[[,]]~~ ;

an optical component positioned between the pulsed laser and the optical means, wherein the light generated by the pulsed laser passes through the optical component, and wherein ~~whereby~~ the optical component ~~spectrally spreads the light passing through~~ is configured to increase said wavelength range of said light to a substantial portion of the entire visible wavelength range; and

means arranged after the optical component for attenuating at least a portion of at least one wavelength of the light emerging from the optical component.

31. (Original) The scanning microscope as defined in Claim 30, wherein the optical component is photonic band-gap material.

32. (Original) The scanning microscope as defined in Claim 31, wherein the photonic band-gap material is configured as a light-guiding fiber.

33. (Original) The scanning microscope as defined in Claim 30, wherein the optical component is configured as a tapered light-guiding fiber.

34. (New) A scanning microscope comprising:

a laser configured to create light having a wavelength range;
an optical means for imaging light generated by the laser onto a specimen;
and
an optical component positioned between the laser and the optical means,
wherein the light generated by the laser passes through the optical
component, and

wherein the optical component is configured to increase said wavelength
range of said light to a range including at least two spectral lines that are
characteristic of different laser types.

35. (New) A scanning microscope comprising:

a laser configured to create light having a wavelength range;
an imaging optics configured to image light generated by the laser onto a
specimen; and
an optical component positioned between the laser and the optical means,
wherein the light generated by the laser passes through the optical
component, and

wherein the optical component is configured to increase said wavelength
range of said light to a range including at least two spectral lines that are
characteristic of different laser types.

36. (New) A scanning microscope comprising:

a laser configured to generate light having a wavelength range;
an imaging optics configured to image light generated by the laser onto a
specimen; and
an optical component positioned between the laser and the optical means,

wherein the light generated by the laser passes through the optical component, and

wherein the optical component is configured to increase said wavelength range of said light to a substantial portion of the entire visible wavelength range.